lyondellbasel	These specifications/special requirement(s) are applicable	
1 1 111 11	specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a	
TANK TRAILER SPECIFICATION	contracted 3PL location as applicable	
PRODUCT	GLYCOL ETHER F	• •
Material Characteristic and i	mmediate hazard	See Product SDS
DOT SPECIFICATION	MC 307, DOT 407, STA	AINLESS STEEL
HEATING/INSULATION	PREFERRED BUT NO	T REQUIRED
GASKET MATERIAL		IN TEFLON, WHITE BUNA, EPDM, **DOME GASKET REE TIGHT SEAL UPON COMPLETION OF LOADING
CONNECTIONS/FITTINGS		LESS STEEL, DUST CAPS W/SEAL PONTS, DOME LID SEALED WITH 1/8" WIRE CABLE SEAL
LIQUID CONNECTION		BOTTOM REAR LOADER, IN-LOADER, CENTER TOMER MAY HAVE SPECIFIC EQUIPMENT
VAPOR CONNECTION - (ATMOSPHERIC VENT) DURING LOADING	CAMLOCK, or KAMLO BUT NOT REQUIRED)	T: 3/4" to 1" BAL VALVE W/BULL PLUG, 2 INCH MALE OK ADAPTER (GRADE LEVEL VAPOR PREFERRED) **IF 2" GLV, DRIVER SHOULD HAVE AN ADAPTER FION OF 3/4" CROWS FOOT.
NITROGEN PADDING	5-7 PSIG	
TANK CLEANLINESS	NOTE: IF TRAILER IS	CLEANING OR RELOAD CERTIFICATE IS REQUIRED. RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING EQUIRED AS PROOF OF PRIOR CARGO.
STRAPPING CHART/DRIVER REQUIREMENTS	YES DRIVER REQUIREME	NTS FOR LYONDELLBASELL SITES
HOSES	FACILITIES. PLEASE REQUIREMENTS FOR	EQUIRED AT LYONDELLBASELL LOADING NOTE: THERE MAY BE SPECIFIC HOSE(S) R CUSTOMER THAT SHOULD BE NOTED IN THE ONS OF THE LYONDELLBASELL SHIPPING
ADDITIONAL APPURTENANCES		D ALWAYS NOTE CARRIER'S INSTRUCTIONS FIELD DCUMENTS FOR ANY ADDITIONAL EQUIPMENT, IENT, ETC.
OTHER	TRANSWIDE CALL-OF MUST ARRIVE AT PIC ALWAYS NOTIFY LYC TO POTENTIAL OF EX	NT AND MATCHING SAP SHIPPING NOTICE, FF, OR CARRIER MANIFEST DOCUMENT. **DRIVER CKUP POINT AT SCHEDULED TIME. **DRIVER MUST DNDELL OF ANY REQUESTED LIGHT LOADING DUE KCEEDING LEGAL GROSS WEIGHT. PLEASE LBASELL LOGISTICS WITH ANY QUESTIONS
PROHIBITED		R WITH EMCO WHEATON FITTINGS, SITE WILL REJECT R ADDITIONAL PERSONNEL UNLESS TEAM DRIVER